GREE

Vireo+

* WIFI CAPABLE

Universal WIFI Kit
Part No. WSBEC02
(sold separately)

Use Part No.

WSBEE03
for 115V only

GREE the Trusted Brand
#1
MANUFACTURER
We are Factory

GREE

MODELS		VIR09AC115V1B	VIR12AC115V1B	VIR09P230V1B	VIR12AC230V1B	VIR18AC230V1B	VIR24AC230V1B	VIR30AC230V1B	VIR36AC230V1B
System Type		Cooling Only	Cooling Only	Cooling Only	Cooling Only	Cooling Only	Cooling Only	Cooling Only	Cooling Only
SYSTEM PERFORMANCE									
Cooling Capacity (min-max)	Btu/h	9,000 (2,764-10,918)	12,000 (3,514-14,569)	9,000 (3,100-9,600)	12,000 (3,100-13,000)	18,000 (6,800-20,000)	22,000 (6,824-27,296)	28,000 (9,485-30,026)	33,600 (7,404-35,997)
Heating Capacity (min-max)	Btu/h	9,900 (2,081-13,989)	12,200 (2,764-16,582)	11,000 (1,911-12,000)	13,000 (2,400-14,000)	19,800 (7,340-23,500)	23,000 (6,824-30,708)	28,400 (9,997-32,994)	34,600 (14,979-35,997)
SEER/EER		23 / 13.0	22 / 12.5	23 / 14.0	22 / 12.5	20 / 12.5	20 / 12.5	18 /10.35	18 /8.2
HSPF/COP								9.0 / 3.0	9.0 / 2.7
Energy Star®		YES	YES	YES	YES	YES	YES	NO	NO
Cooling Temperature Range	°F	0 – 115	0 – 115	0 – 115	0 – 115	0 – 115	0 – 115	0 – 115	0 – 109
Heating Temperature Range	°F							-4 – 75	-4 – 75
INDOOR UNIT									
Air flow (min-max)	CFM	171-377	171-400	171-377	171-400	335-559	530-706	412-706	412-736
Sound Level (min-max)	dB(A)	26-43	28-45	29-43	29-45	39-47	36-48	37-51	37-54
Dehumidification	pt/hr	1.7	3.0	1.7	3.0	3.8	4.2	6.3	7.4
Unit Dimension (WxHxD)	in	33.4 x 11.4 x 8.2	33.4 x 11.4 x 8.2	33.4 x 11.4 x 8.2	33.4 x 11.4 x 8.2	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7	53.1 x 12.8 x 10.0	53.1 x 12.8 x 10.0
Package Dimension (WxHxD)	in	36.3 x 14.9 x 11.1	36.3 x 14.9 x 11.1	36.3 x 14.9 x 11.1	36.3 x 14.9 x 11.1	41.0 x 15.1 x 12.6	45.2 x 16.3 x 13.8	56.7 x 16.6 x14.1	56.7 x 16.6 x14.1
Weight (Net/Gross)	lbs	23.2 / 27.6	23.2 / 27.6	22.1 / 26.5	22.1 / 26.5	28.7 / 35.3	34.2 / 41.9	41.9 / 51.8	41.9 / 51.8
OUTDOOR UNIT									
Compressor Type		G10 INVERTER DRIVEN ROTARY							
Sound Level (min-max)	dB(A)	53	53	53	54	55	59	62	65
Unit Dimension (WxHxD)	in	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	37.6 x 27.6 x 15.6	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8
Package Dimension (WxHxD)	in	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	40.5 x 29.5 x 18.0	42.6 x 33.7 x 19.2	42.6 x 33.7 x 19.2	42.6 x 33.7 x 19.2
Weight (Net/Gross)	lbs	71.7 / 77.2	77.2 / 83.8	78.3 / 83.8	86.0 / 92.6	114.7 / 124.6	142.2 / 153.2	154.4 / 165.4	161.0 / 172.0
Refrigerant Charge - R410A	oz	42.3	47.6	45.9	47.6	56.4	77.6	84.7	91.7
Coil Type		Copper / Alumimum with Gold FIN Coating							
INSTALLATION									
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 1/2	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8
Pre-Charge Length	ft	25	25	25	25	25	25	25	25
Max. Line Run	ft	49	66	49	66	82	82	98	98
Max. Elevation	ft	33	33	33	33	33	33	33	33
ELECTRICAL									
Voltage / Phase / Hertz		115V /1/ 60Hz	115V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz
Rated Current Cooling	amps	11.3	11.5	5.8	6.0	6.9	14.5	17.0	20.0
Rated Current Heating	amps	10.7	12.0	6.0	6.3	8.4	14.5	17.5	20.0
MCA	amps	12	17	9	9	16	20	20	24
MOCP	amps	20	25	15	15	25	30	30	40
Interconnecting Wire		AWG16 / 4							
Limited Warranty		10 Yr on Compressor 5 Yr on Parts							

Test conditions are based on AHRI 210/240.

1. Rating conditions (cooling)-Indoor: D.B. 80° F (27° C), W.B. 67° F (19° C); Outdoor: D.B. 95° F (35° C), W.B. 75° F (24° C). Rating conditions (heating)-Indoor: D.B. 70° F (21° C), W.B. 60° F (16° C); Outdoor: D.B. 47° F (8° C), W.B. 43° F (6° C).

AHRI CERTIFIED™ www.ahridirectory.org

ETL LISTED US

PROMOCIÓN 10 AÑOS EN COMPRESOR 5 AÑOS EN PARTES GARANTÍA

R-410A REFRIGERANT

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or change at any time, specifications or designs without notice or without incurring obligations.©2018. All rights reserved. Cat No.Gree_Vireo

Low Voltage Start -up

Fin Corrosion Coil Protection

High Temp Resistance PCB Up To 185F

Photocatalytic and Silver Ion Filter Eliminate 99.9% of Bacteria, Viruses and unpleasant odors.

www.greepr.com